

NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD

CLOSURE OF WASTE IMPOUNDMENTS

(Each)

CODE 360

DEFINITION

The closure of waste impoundments (treatment lagoons and liquid storage facilities), that are no longer used for their intended purpose, in an environmentally safe manner.

PURPOSE

- Protect the quality of surface water and groundwater resources.
- Eliminate a safety hazard for humans and livestock
- Safeguard the public health.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to agricultural waste impoundments that are no longer needed as a part of a waste management system and are to be permanently closed or converted.

Where these impoundments are to be converted to fresh water storage and the original impoundment was not constructed to NRCS standards, this practice will only apply where the investigation, as required in National Engineering Manual (NEM) 501.23, shows structural integrity.

CRITERIA

General Criteria Applicable to All Purposes

The closure shall comply with all Federal, State, and local laws, rules, and regulations including pollutant discharge elimination system requirements.

All structures used to convey waste to waste impoundments or to provide drainage from the

impoundment area shall be removed and replaced with compacted earth material or otherwise rendered unable to convey waste.

Liquid and slurry wastes shall be agitated and pumped to the extent conventional pumping will allow. Clean water shall be added as necessary to facilitate the agitation and pumping. The wastewater shall be utilized in accordance with NRCS Conservation Practice Standard, Waste Utilization, Code 633 and **Nutrient Management, Code 590**. The sludge remaining on the bottom and sides of the waste treatment lagoon or waste storage facility may remain in place if it will not pose a threat to the environment. If leaving the sludge in place would pose a threat, it shall be removed to the fullest extent practical and utilized in accordance with NRCS Conservation Practice Standard, Waste Utilization, Code 633 and **Nutrient Management, Code 590**. Soil laden with manure on the bottom and side slopes of the impoundment shall be removed and properly disposed.

Concrete or synthetic liners may be buried in the existing facility if all of the following requirements are met:

- Liner is broken up or holes are made to allow movement of water through the profile after the facility is closed.
- Test pits or soil borings are made below the liner to check for soil mixed with waste. If soil mixed with waste is present, the liner must be pulled back to allow the removal waste laden soil. The liner material may then be buried in the closed facility. If the liner is removed from the facility it must be disposed of in accordance to all local, state and federal laws and regulations.

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.

Pressure treated lumber shall not be buried and must be properly disposed of in a landfill.

Land Reclamation. Impoundments with embankments may be breached so that they will no longer impound water, and excavated impoundments **shall** be backfilled so that these areas may be reclaimed for other uses. Waste impoundments that have water impounded against the embankment are considered embankment structures if the depth of water is three feet or more above natural ground.

- (1) **Embankment Impoundments.** Waste shall be removed from the site before the embankment is breached. The slopes and bottom of the breach shall be stable for the soil material involved, however the side slopes shall be no steeper than three horizontal to one vertical (3:1). **All contaminated runoff from the construction site shall be contained and disposed of in an environmentally sound manner.**
- (2) **Excavated Impoundments.** The backfill height shall exceed the design finished grade by 5 percent to allow for settlement. The top one foot of the backfill shall be constructed of the most clayey material available and mounded to shed rainfall runoff. Incorporate available topsoil where feasible to aid establishment of vegetation.
- (3) **Both embankment and excavated impoundments shall be excavated, backfilled, filled in, compacted, graded, etc. to the elevations and contour necessary so that surface water can drain freely from the entire site.**
- (4) **Existing perimeter drains shall meet NRCS code 606, Subsurface Drainage. The perimeter drain can be diverted into the convert pond to help supply water. Perimeter drains shall be monitored for water quality. If perimeter drains show continuous evidence of poor water quality, the drainage shall be collected and treated or properly disposed.**

Closed waste storage structures shall be demolished or disassembled or otherwise altered to such an extent that no water can be impounded. Disassembled materials such as pieces of metal shall be temporarily stored until their final disposition in such a manner that they do not pose a hazard to animals or humans.

Demolished materials shall be buried on-site or moved off-site to locations designated by state or local officials. If buried on-site, the materials are to be covered with soil to a settled depth of one foot, and the backfill be sufficiently mounded such that runoff will be diverted from the site after the backfill settles.

Conversion to Fresh Water Storage. The converted impoundment shall meet the requirements as set forth in NRCS practice standard 378 – Pond. **Water from the fresh water pond conversion shall meet all federal, state and local requirements. The discharge from the converted fresh water pond shall be collected and monitored. Water shall not be discharged until all water quality requirements (tests) are met.**

Safety. When sludge is not removed from a waste impoundment that is being converted to fresh water storage, the impoundment shall not be used for fish production, swimming, or livestock watering until water quality is adequate for these purposes. Precautions (fencing and warning signs) shall be used to ensure that the facility is not used for purposes incompatible with the current quality of water.

Personnel shall not enter an enclosed waste impoundment without breathing apparatus or taking other appropriate measures.

Protection. All disturbed areas shall be re-vegetated or other suitable measures used to control erosion and restore the esthetic value of the site. Sites not suitable for re-vegetation through normal cropping practices shall be vegetated using NRCS Conservation Practice Standard, Critical Area Planting, Code 342.

Measures shall be taken during construction to minimize site erosion and pollution of downstream water resources. This may include such items as silt fences, hay bale barriers, temporary vegetation, and mulching.

CONSIDERATIONS

Reduce pumping effort to empty waste impoundments where the surface is covered by a dense mat of floating vegetation by first applying herbicide to the vegetation and then burning the residue. Appropriate permits must be obtained before burning.

Alternative methods of sludge removal may be required where the impoundments contain large amounts of oyster shells, soil, or other debris.

Minimize the impact of odors associated with emptying and land applying wastewater and sludge from a waste impoundment by using an incorporation application method at a time when the humidity is low, when winds are calm, and when wind direction is away from populated areas.

Soil to fill excavated ponds should not come from important farmlands (prime, statewide, local, and/or unique).

Breeched embankments may detract from the overall esthetics of the operation. Embankments should be removed and the site returned to its original grade.

Keep sludge left in place covered with water to prevent its aerobic decomposition with the potential release of nutrients to surface and ground water.

Disassembled structural facilities may be suitable for assembly at another site. Care should be taken during closure to minimize damage to the pieces of the facility, particularly coatings that prevent corrosion of metal pieces.

The construction of buildings or other facilities should not be considered in the area of the impoundment closure until the area is allowed to settle for several years.

PLANS AND SPECIFICATIONS

Plans and specifications for closure of abandoned waste treatment lagoons and waste storage facilities shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose. The plans and specifications shall also be consistent with the requirements of that standard. The approximate location of the waste storage facility which was removed and any tile outlets shall be maintained in the cooperator file.

OPERATION AND MAINTENANCE

An operation and maintenance (O&M) plan shall be prepared for the closure of the waste impoundment and any other associated conservation practices. The owner shall sign the O&M plan to indicate an understanding of the requirements and commitment to operate and maintain this practice as specified. The proper closure of a waste treatment lagoon or waste storage facility should require little or no operation and maintenance; however, if it is converted to another use, such as a fresh water facility, operation and maintenance shall be in accordance with the needs as set forth in the appropriate NRCS conservation practice standard for the intended purpose.